



US006433851B2

(12) **United States Patent**
Shimada et al.

(10) **Patent No.:** **US 6,433,851 B2**
(45) **Date of Patent:** **Aug. 13, 2002**

(54) **TRANSMISSION TYPE LIQUID CRYSTAL
DISPLAY HAVING A TRANSPARENT
COLORLESS ORGANIC INTERLAYER
INSULATING FILM BETWEEN PIXEL
ELECTRODES AND SWITCHING**

(75) **Inventors:** Takayuki Shimada, Yamatokoriyama;
Masaru Kajitani, Osaka; Masaya
Okamoto, Soraku-gun; Naofumi
Kondo; Mikio Katayama, both of
Ikoma; Yoshikazu Sakuhana,
Yamatokoriyama; Akhiro Yamamoto,
Tenri; Yukinobu Nakata, Tenri;
Hirohiko Nishiki, Tenri, all of (JP)

(73) **Assignee:** Sharp Kabushiki Kaisha, Osaka (JP)

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/757,477

(22) **Filed:** Jan. 11, 2001

Related U.S. Application Data

(62) Division of application No. 09/592,857, filed on Jun. 12,
2000, now Pat. No. 6,195,138, which is a division of
application No. 09/110,134, filed on Jul. 6, 1998, now Pat.
No. 6,097,452, which is a continuation of application No.
08/695,632, filed on Aug. 12, 1996, now Pat. No. 6,052,162.

(30) Foreign Application Priority Data

Aug. 11, 1995 (JP) 7-206367
Sep. 29, 1995 (JP) 7-254043

(51) **Int. Cl.⁷** G02F 1/333; G02F 1/136

(52) **U.S. Cl.** 349/138; 349/42

(58) **Field of Search** 349/44, 38, 39,
349/42, 43, 138, 139; 430/176; 345/92,

87

(56) References Cited

U.S. PATENT DOCUMENTS

3,602,782 A	*	8/1971	Klein	317/235
4,688,896 A		8/1987	Castleberry	349/55
4,759,610 A		7/1988	Yanagisawa	349/162
4,857,907 A		8/1989	Koden	349/140

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 117 957	9/1984
EP	0 611 812	8/1994
EP	0 632 229	1/1995

(List continued on next page.)

OTHER PUBLICATIONS

Patent Abstracts of Japan, vol. 016, No. 218, May 21, 1992
& JP-A-04 042214, Feb. 12, 1992.

(List continued on next page.)

Primary Examiner—William L. Sikes

Assistant Examiner—Tarifur R. Chowdhury

(74) *Attorney, Agent, or Firm*—Nixon & Vanderhye P.C.

(57)

ABSTRACT

The transmission type liquid crystal display device of this invention includes: gate lines; source lines; and switching elements each arranged near a crossing of each gate line and each source line, a gate electrode of each switching element being connected to the gate line, a source electrode of the switching element being connected to the source line, and a drain electrode of the switching element being connected to a pixel electrode for applying a voltage to a liquid crystal layer, wherein an interlayer insulating film formed of an organic film with high transparency is provided above the switching element, the gate line, and the source line, and wherein the pixel electrode formed of a transparent conductive film is provided on the interlayer insulating film.

24 Claims, 13 Drawing Sheets

